



Product Application & Results

1997 American Blvd. • P.O. Box 5606 • De Pere, WI 54115-5606 • 800.225.2231 • Fax: 920.337.9410

PRODUCT: **Advantage[®]** **Stock # 1220**

Description: High alkaline concentrated liquid presoak and high pressure detergent. Designed for frictionless systems, but also aids cleaning in hybrid and friction systems. In addition, Advantage[®] contains special surfactants that help clarify reclaim systems.

Color: Green

Scent: Mild

Foaming Ability: Low to Moderate

<u>Features</u>	=	<u>Benefits</u>
Titrateable	=	Quickly determine dilution
Biodegradable	=	Acceptable to waste water treatment.
Reclaim Clarifier	=	Settles small particles from reclaim water giving longer runs between filter cleaning and less wear on nozzles and pumps.
Highly Effective	=	Excellent removal of dirt, oils, and road film.

<u>Application</u>	<u>Dilution Ratios</u>		
	<u>Strongest</u>	<u>Weakest</u>	<u>Average</u>
<u>Frictionless Systems</u>			
High Pressure cleaning & Prep Guns	1:250	1:500	1:350
Foam or Spray - Low-pressure presoak	1:40	1:100	1:60
Bumper Prep	1:40	1:60	1:45
<u>Friction & Hybrid Systems</u>			
High Pressure cleaning & Prep Guns	1:250	1:500	1:350
Foam or Spray – Low-pressure presoak	1:80	1:200	1:100
Bumper Prep	1:40	1:80	1:50

Required strength of product dilution will vary depending on cleaning conditions and type and condition of equipment used.

Guidelines for Application

Water Quality: Use SOFT WATER for best performance! In hard water (over 0 grains) increase strength by 10% for each grain of water hardness (1:60 + 10% = 1:54). Trying to clean in frictionless washes with water over 2 grains of hardness is not recommended.

Solution Temperatures: Summer: 70-90°F, Winter: 90-140°F. This product works at peak performance when the temperature of the diluted solution on the vehicle surface is between 100-110°F. Product performance is reduced at surface temperatures over 120°F.

PRODUCT:

Advantage[®]

Stock # 1220

Guidelines for Application (continued)

Dwell time: Recommend from 15 to 25 seconds between presoak and high-pressure rinse. Decrease dwell time if vehicles are hot to avoid increasing the product concentration through evaporation of the water.

Economy: Reduce volume through alternative nozzling, equipment changes. Do not over-heat dilution water as it wastes energy and can decrease product effectiveness.

Alternative Products

The Option[®] One Step Plus[™] lower cost alternative presoaks without reclaim abilities.

Performix[®] Premium stronger alkaline presoak with reclaim settling abilities.

The EDGE[®] High alkaline presoak with a Bold & Fresh scent.

Titration Chart For Advantage[®]		
This chart uses the "Standard Alkaline Titrant" and a water blank must be titrated to subtract from your total drops before comparing to the curve.	Dilution	Drops
	1:30	39
	1:40	29
	1:50	24
	1:60	20
	1:70	17
	1:80	15
	1:100	12
	1:125	10
	1:150	8
	1:200	7
1:400	4	