



Product Application & Results

1997 American Blvd. • P.O. Box 5606 • De Pere, WI 54115-5606 • 800.225.2231 • Fax: 920.337.9410

PRODUCT: **Pearl® Sealant & Drying Agent** **Stock # 2300**
 Pearl® Sealant & Drying Agent-Lemon **2301**

Description: Concentrated Sealer/Drying Agent that is economical and versatile. For use in all types of washes and all appropriate applications.

Color: Natural
Scent: Mild sealant or Lemon

<u>Features</u>	=	<u>Benefits</u>
Concentrated	=	Low cost per car
Versatile	=	Works well in all applications, high or low pressure.

<u>Application</u>	<u>Dilution Ratios</u>			<u>Oz. / Car</u>
	<u>Strongest</u>	<u>Weakest</u>	<u>Average</u>	
High Pressure Sealant	1:1000	1:1500	1:1250	1 -2
Drying Agent & Low Pressure Sealant	1:150	1:400	1:250	1-1.5

Required strength of product dilution will vary depending on conditions and type of equipment used.

Guidelines for Application

Water Quality: Mix only with fresh water, never use reclaimed water.

Solution Mix with cold water, warm water will not improve performance of this product.
Temperatures:

Surface Vehicle should be clean and well rinsed prior to applying **Pearl®**
Preparation: **Sealant & Drying Agent.**

Dwell Time: A "set rinse" may be applied within a few seconds of this application. Line speed should be adjusted to allow water to bead before entering the blower.

PRODUCT: **Pearl[®] Sealant & Drying Agent** **Stock # 2300**
 Pearl[®] Sealant & Drying Agent-Lemon **2301**

Guidelines for Application - Continued

Economy: Adjust dilution to get the desired water beading at the greatest economy. While low pressure, low volume systems are the most efficient at applying sealants and drying agents in general, **Pearl[®] Sealant & Drying Agent** works better under high pressure than most other similar products.

Special Instructions

A build-up of separated product may occur in Hydrominder tanks at washes that are not very busy. Keep volume of premixed product to a minimum by adjusting the Hydrominder float level. Alternatively change to a chemical feed pump, or switch to another CSI product.

Note: This product contains solvents that can evaporate from open containers, causing the product to thicken and become difficult to draw. Minimize evaporation by keeping container closed when not in use and running draw tubes through bungs/caps that are drilled to accommodate the draw tube. Purchase this product in package sizes that will be completely used, once opened, within three months.

Alternative Products

Drying Agents: "Dri-MaxTM", or "FBX-5TM"

Sealants: "ProShield[®]" for tunnels & automatics.

"Spectrum[®] Clear Coat Sealant" for self-serve washes.