



Product Application & Results

1997 American Blvd. • P.O. Box 5606 • De Pere, WI 54115-5606 • 800.225.2231 • Fax: 920.337.9410

PRODUCT: **ProShield®** **Stock # 2402**
ProShield® Pina Colada **2406**

Description: Clear coat sealant with Ultraviolet sunray protection and long lasting wash resistant durability. **ProShield®** can be applied successfully through all types of application equipment.

Color: Aqua-blue
Scent: Mild also available in Pina Colada
Foaming ability: None

<u>Features</u>	=	<u>Benefits</u>
UV Protection	=	Protects finish from sun
Wash Resistance	=	Long lasting
Brighteners	=	Improves shine on cars
Marketing materials	=	Increased extra service sales
Scented option	=	Increased customer appeal

Applications / Dilution Ratios

Since high dilution ratios are difficult to determine and adjust accurately, set up **ProShield®** to draw about ¾ ounce per vehicle in low volume applications. In high volume systems, start at 1 ounce per vehicle. Adjust concentration to achieve the desired beading action and vehicle shine.

	<u>Dilution Ratio</u>	<u>Ounces per Car</u>
High Pressure	1:1000 to 1:1500	¾ to 1¼ oz.
Low Pressure	1:400 to 1:500	½ to ¾ oz

Guidelines for Application

Water Quality: Mix only with fresh water, never use reclaimed water.
Solution Mix standard **ProShield®** with cold water, as warm water will not improve the performance of this product. However warm water will enhance the fragrance in the scented version of this product.
Temperatures:
Surface Vehicle should be clean and rinsed prior to applying **ProShield®**.
Preparation:
Dwell Time: A "set rinse" can be applied within a few seconds of the **ProShield®** application. Line speed should be adjusted to allow water to bead before entering the blower area.

PRODUCT:

**ProShield®
ProShield® Pina Colada**

**Stock # 2402
2406**

Economy: Adjust dilution to get desired water beading at the greatest economy. While low pressure, low volume systems are the most efficient at applying clear coat sealants **ProShield®** works better under high pressure and high volume than most other sealants.

Special Instructions

Often used following CSI **LustraFoam®** foaming polish as part of a higher value extra service packages. When used immediately after **LustraFoam®** it is best to apply **ProShield®** with sufficient volume to ensure proper rinsing of the foam from the vehicle.

LustraFoam® and **ProShield®** together have the most comprehensive CSI marketing materials available.

Note: This product contains solvents that can evaporate from open containers, causing the product to thicken and become difficult to draw. Minimize evaporation by keeping container closed when not in use and running draw tubes through bungs/caps that are drilled to accommodate the draw tube. Purchase this product in package sizes that will be completely used, once opened, within three months.