



Product Application & Results

1997 American Blvd. • P.O. Box 5606 • De Pere, WI 54115-5606 • 800-225-2231 • Fax: 920-337-9410

PRODUCT: Ultraflex[®] Sealant 421 Tropical Fruit Stock# UF421

Description: Ultra-Concentrated clear coat sealant with ultraviolet sun protection and long lasting wash resistant durability. **UltraFlex[®] 421** can be applied successfully through all types of application equipment.

Color: Aqua **Scent:** Tropical Fruit **Foaming Ability:** Low

<u>Features</u>	=	<u>Benefits</u>
Ultra-Concentrated	=	Lower cost per car – Space Saving
Brighteners	=	Improves shine on cars
Fresh Fruity Fragrance	=	Increased customer appeal
Unscented	=	Meter with your choice of fragrance
UV Protection	=	Protects finish from the sun

Applications Rates

Unscented Applications: UltraFlex[™] Sealant 421 should be drawn direct applying 5-10 ml per vehicle to desired performance.

For Self-Serve High-Pressure Sealant start with a Brown Hydrominder Tip, evaluate and adjust as desired.

<u>Application</u>	<u>Dilution Ratios</u>		
	<u>Strongest</u>	<u>Weakest</u>	<u>Average</u>
Low-Pressure	1:800	1:1200	1:1000
High-Pressure	1:1500	1:6000	1:3000

Guidelines for Application

Water Quality: Mix only with fresh water, never use reclaimed water.

Solution Mix with cold water, as warm water will not improve the

Temperature: performance of this product. However warm water will enhance the fragrance loft.

Dwell time: A "Set Rinse" or "Spot-Free Rinse" can be applied within a few seconds of the **UltraFlex[™] Sealant 421** application.

Special Tubing Requirement: Certain chemical ingredients react with standard vinyl tubing so we recommend the use of Tygon-2275 tubing with this Ultraflex[®] application. Use CSI Ultraflex[®] Part Number: P20010001-050 for a 50 ft roll of the proper tubing.



Product Application & Results

1997 American Blvd. • P.O. Box 5606 • De Pere, WI 54115-5606 • 800-225-2231 • Fax: 920-337-9410

Viscosity / Temperature Relationship: Temperature changes have little effect on the viscosity of this product. Few tip adjustments due to temperature changes should be necessary.

UF421-0112 p.2