



# Product Application & Results

1997 American Blvd. • P.O. Box 5606 • De Pere, WI 54115-5606 • 800-225-2231 • Fax: 920-337-9410

**PRODUCT:** Ultraflex® Wall Cleaner 700 **Stock # UF700**

**Description:** Concentrated foaming acidic wall cleaner, best used to clean bricks, blocks, stainless steel, ceramic tiles, painted walls and fiberglass panels. Contains highly effective mixture of acids and surfactants for speedy cleaning, corrosion protection and economy. Dissolves minerals and penetrates dirt deposits on surfaces.

**Color:** Colorless

**Scent:** Mild

**Foaming Ability:** High

**Features**

Attacks mineral soils  
Non-Fluoride  
High Foaming  
Highly reactive

= **Benefits**

= Performs in tough conditions.  
= Safer than HF products.  
= Customer appeal.  
= Reduced cleaning time.

**Application**

**Dilution Ratios**

	<b><u>Strongest</u></b>	<b><u>Weakest</u></b>	<b><u>Average</u></b>
Car Wash Tunnel/Bay Wall and Equipment Very dirty Conditions	1:3	1:6	1:5
Routine maintenance	1:6	1:12	1:9

**Guidelines for Application**

**Water Quality:** Soft water is best for dilution but not necessary.

**Solution Temperatures:** Cleaning will improve if applied with warm (100°F) water. Warm water is especially recommended in colder weather.

**Dwell time:** Allow a maximum possible dwell time, then follow with scrubbing on tougher soils and follow with high-pressure rinse.

**Special Instructions:** Mix product at dilution ratios listed in application section. Product may be used stronger for hard to clean environments.